

**SASO 2884: 2017 ENERGY
EFFICIENCY INFORMATION**



A.O. Smith Brand Model Number	Declared Load Profile	Energy Efficiency Class	Bar Color	Rated Energy Efficiency %	Rated Annual Electricity Consumption (kWh/year)	Thermostat Temperature Setting (Celsius)	Rated Capacity (Liters)	Rated Thermal Losses/Qpr (kWh)	Rated Voltage Range	Rated Frequency (Hz)	Rated Power Input (kW)	Rated Current (amps) (at 230V)	Rated Mixed Qty of Water/V40 (Liters)
ECT-52X 290	XL	D	Yellow	94	4510	48.8°C	170	1.69	220-240	50/60	4.5	19.56	345
ECT-55X 290	2XL	E	Orange	92	5890	48.8°C	205	2.05	220-240	50/60	4.5	19.56	375
ECT-66X 290	2XL	E	Orange	91	5995	48.8°C	225	2.5	220-240	50/60	4.5	19.56	410
ECT-80X 290	2XL	E	Orange	90	6050	48.8°C	275	2.7	220-240	50/60	4.5	19.56	500
ECT-120X 290	3XL	D	Yellow	94	10955	48.8°C	400	2.75	220-240	50/60	4.5	19.56	715
ECS-30X 290	L	D	Yellow	92	2810	48.8°C	100	1.32	220-240	50/60	4.5	19.56	200
ECS-40X 290	XL	D	Yellow	94	4495	48.8°C	135	1.62	220-240	50/60	4.5	19.56	265
EJC-6 290	S	F	Red	68	700	48.8°C	20	1.29	220-240	50/60	1.5	6.52	40
EJC-10 290	S	F	Red	68	695	48.8°C	30	1.26	220-240	50/60	1.5	6.52	80
EJCS-20 290	M	E	Orange	81	1625	48.8°C	65	1.81	220-240	50/60	2.5	10.87	120
EJCS-20-030 290	M	E	Orange	81	1620	48.8°C	65	1.81	220-240	50/60	3.0	13.04	120
EJCT-20 290	M	E	Orange	82	1595	48.8°C	65	1.65	220-240	50/60	2.5	10.87	130

NOTICE: Keep this insert sheet with the water heaters manual for you or future users.